

Date of Publication: 08/10/2018

Identification

Manufacturers details

Product name : Eva-Last® Infinity™ co-extruded composite deck

board.

Product use: This product is primarily used for deck boards and

other timber replacement items.

Manufacturers information: Eva-last® Distributors

Room 1203, 12/F Tower 3 33 Canton Road, Tsimshatsui Hong

Kong, China

Emergency Contact: +27 10 593 9220 Product information: +27 10 593 9220

Supplier and product support details

Supplier: ITI AUS (Australia)

Supplier information: danek@iti.net.au

Emergency contact: 02 8805 5000

Product information: 02 8805 5000

Hazard identification

This material is a non-hazardous.

Emergency overview:

Keep away from contact with oxidizing materials. Dust may form an explosive mixture with air. Use exhaust ventilation when cutting, sawing or grinding in an enclosed area. Dust may cause irritation to eyes, skin, and upper respiratory tract. When cutting, sanding, or grinding avoid inhalation and wear safety glasses. Use puncture resistant gloves. Wash thoroughly after handling should irritation occur.

Composition and information on ingredients

SUBSTANCE NAME	APPROX WEIGHT %	CAS#	AGENCY	EXPOSURE LIMITS	COMMENTS
Bamboo fibre	55 - 60%	N/A	OSHA OSHA ACGIH ACGIH	PEL-TWA 15 mg/m³ PEL-TWA 5 mg/m³ TLV-TWA 3 mg/m³ TLV-STEL 10 mg/m³	Total dust Respiratory dust fraction Respiratory dust fraction Inhabitable particles
HDPE - polyethylene	35 - 40%	9002-99-4	N/A	N/A	Thermoplastic
Additives					
Cap		N/A	N/A	N/A	Trade secret
Anti mould agent					
Coupling agent					
Anti UV agent					
Colour pigment					



NOTE:

Bamboo is a species of the grass family which has distinct anatomical differences from that of timber. Therefore, bamboo would be regulated as an organic dust in a category known as "Particulates Not Otherwise Regulated" (PNOR), or Nuisance Dust by OSHA. The ACGIH classifies dust or particulate in this category as "Particulates Not otherwise Specified". Bamboo fibres in Eva-Last® Infinity™ boards are contained in a High-Density-Polyethylene (HDPE) Matrix, consisting mainly of polyethylene plastic and bamboo fibre. HDPE is a thermoplastic materials. HDPE may be sourced as both virgin and recycled materials. Standard material consists of 40 % HDPE and 60 % bamboo fibres.

First aid measures

Eye contact:

Following exposure to dust: flush thoroughly with water. If irritation occurs, call a physician.

Skin contact:

Exposure to dust is not expected to be a problem. If irritation does occur, wash contact areas with soap and water. Launder contaminated clothing before reuse.

Inhalation:

If respiratory issues such as extensive coughing, shortness of breath, wheezing or chest tightness occurs after exposure to dust, avoid further exposure and seek immediate medical assistance.

Ingestion:

Small amounts of ingestion of the material are not usually problematic. However, if uncomfortable, seek medical assistance.

Firefighting measures

Extinguishing media to keep on hand:

Water, foam, dry chemical.

Special fire-fighting procedures:

Use extinguishing media most appropriate for fire type. Douse affected and surrounding areas with water in normal circumstances. For fires in enclosed areas, firefighters must use self-contained breathing apparatus and suitable protective gear.

Special protective equipment:

For fires in enclosed areas, firefighters must use self-contained breathing apparatus. The product will produce smoke once ignited.

Unusual fire and explosion hazards:

High dust levels may lead to the potential for explosions in certain conditions.

NFPA hazard ID:

Health: 0, Flammability: 1, Reactivity: 0.

Hazardous decomposition product:

If ignited, smoke, carbon dioxide, carbon monoxide, and other harmful gases may be emitted.



Accidental release measures

Where dusty conditions are created as a result of cutting or sawing, wet the saw dust down then sweep or vacuum for disposal. Personnel performing clean-up must use protective appropriate equipment such as dust masks.

Handling and storage

Notification procedures

- Bamboo plastic composite is heavier than normal wood. Remember to use safe lifting procedures.
- Boards should be stored undercover.
- When storing boards on site, a pallet should be used. Or the boards should be on a flat surface.
- A groundsheet may be used if there is no other option.
- Boards should be securely packed. Do not over-stack as this may result in unstable loads that may cause injury.
- Keep away from oxidisers and hazardous chemicals.
- Keep away from areas with excessive heat or open flames.

Personnel precautions:

Boards are long and heavy. Care must be taken when lifting. More than one person may be required to lift dependent on the length of the board.

Exposure controls and personal protection measures

Ventilation:

Use with adequate ventilation in processing operations. This product is designed for external use. In most circumstances natural outdoor ventilation should suffice without further special requirements.

Respiratory protection:

Approved dust respirators must be used for dusty conditions or if inhalation of dusts is likely. There are no requirements under ordinary conditions of use and with adequate ventilation.

Eye protection:

Safety glasses with side shields, or goggles, should be worn to protect against dust particles when operating tools.

Skin protection:

No special equipment required under normal circumstances.

National occupational exposure limits: No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

Biological limit values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit

Personal protection equipment: OVERALLS, SAFETY SHOES

Wear standard safety equipment - overalls and safety shoes. If risk of dust inhalation exists, use respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.



Physical and chemical properties

Physical properties		Measured value	Result	Note		
Appearance		Planks are supplied in various colours and finishes				
Linear thermal expansion coefficient		45.37 10 ⁻⁶ K ⁻¹	Requirement fulfilled	Temperature range of - 20 °C to 60 °C		
Bulk density		1390 kg/m³	For information			
Flame spread index		110	Pass	<=200		
Smoke emissions		500	Pass	N/A		
Termite resistance		Mass loss ~ 0.02 %	Pass			
Fungal decay resistance	G.trabeum	Mass loss ~ 0.77%	Pass	Requirement fulfilled		
	P.Placenta	Mass loss ~ 0.91%	Pass			
	T. versicolor	Mass loss ~ 0.90%	Pass			
	I.lacteus	Mass loss ~ 0.91%	Pass			

Stability and reactivity

• Stability:

Stable

• Conditions to avoid:

Extreme heat and flame, build up of dusts and debris

• Incompatibility (materials to avoid):

Strong oxidisers

• Decomposition products:

Carbon monoxide and carbon dioxide if ignited

• Hazardous polymerization:

Will not occur

Toxicological information

This material has been evaluated against the SVHC (substance of very high concern) list. There are no hazardous chemicals present. For a full list, please contact www.eva-last.com.

Substances on REACH SVHC list are:

- substances meeting the criteria for classification as carcinogenic, mutagenic or reprotoxic (CMR) category 1 or 2;
- persistent, bioaccumulative and toxic (PBT) substances; or
- very persistent and very bioaccumulative (vPvB) substances;
- substances for which there is evidence for similar concern, such as endocrine disruptors



Ecological information

Environmental fate and effects:

No foreseeable environmental effects

Disposal considerations

Environmental fate and effects:

Products are not listed as hazardous waste and can be disposed of in accordance with local, state, and national regulations.

Transport information

Air transport:

Not classified as dangerous goods by the International Air Transport Association (IATA).

Road and rail transport:

Not classified as dangerous goods by the Australian Dangerous Goods Code (ADG).

Marine transport

Not classified as dangerous goods by the International Maritime Dangerous Goods Code (IMDG).

Regulatory information

Poisons schedule (Aust): not applicable

Other information

Document disclaimer:

The provided information is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond the control of Eva-Last®. The user, therefore, assumes all risks of use of the product and Eva-Last® expressly disclaims all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Nothing is intended as a recommendation for uses, which infringe valid patents, or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or re-transmission of this document, in whole or in part, is not permitted. Eva-Last® assumes no responsibility for accuracy of information unless the document is the most current available from an official member of Eva-Last®.

Utilization disclaimer:

Eva-Last® composite has been designed to meet industry norms. However, building codes and standards may differ between varying jurisdictions/countries. Before installation of Eva-Last® composite ensure that your installation plans are in accordance with local building codes, or consult an expert. Please see our website www.eva-last.com for further information.